

Sunstone 2017 Product Catolog



Weld Heads



Weld Attachments



Accessories





TABLE OF CONTENTS

| Pulse-Arc Welders |
|----------------------------------|
| Pulse-Arc Welder Electrodes |
| Pulse-Arc Welder Accessories |
| Laser Welders7 |
| Laser Engravers/Cutters7 |
| Pulse-Arc Copper Welding Systems |
| DC Resistance Welders |
| CD Resistance Welders |
| AC Resistance Welders |
| Resistance Welding Weld Heads11 |
| Resistance Welding Attachments12 |
| Resistance Welding Electrodes15 |
| Resistance Welding Accessories |
| Battery Welding Accessories |



PART NUMBER

DESCRIPTION

| PULSE ARC W | ELDERS | |
|--------------------------------|--|--|
| Orion 250i ² Welder | Orion 250 i ² Welding Power Supply, (welder, swing arm, microscope and all acc. come in one box). | |
| Orion 200i ² Welder | Orion 200 i ² Welding Power Supply, (welder, swing arm, microscope and all acc. come in one box). | |
| Orion 250s Arm | Orion 250s Micro Pulse Arc Welder with Free-Floating Microscope Package (Orion Arm) (2 boxes) | |
| Orion 250s Base | Orion 250s Micro Pulse Arc Welder & Base Microscope Lens Package (2 boxes) | |
| Orion 250s ADL | Orion 250s Micro Pulse Arc Welder & Darkening Lens Package (2 boxes) | |
| Orion 150s Arm | Orion 150s Welding Power Supply with Swing Arm (2 boxes) | |
| Orion 150s Base | Orion 150s Welding Power Supply with Base Microscope (2 boxes) | |
| Orion 150s ADL | Orion 150s Welding Power Supply with Darkening Lens (2 boxes) | |

PART NUMBER DESCRIPTION

PRODUCT PICTURE

| Orion 100c Arm | Orion 100c Swing Arm Microscope Package and Accessories (2 boxes) | |
|---------------------------------|--|--|
| Orion 100c Base | Orion 100c Base Microscope Package and Accessories (2 boxes) | |
| Orion 100c ADL | Orion 100c Darkening Lens Package and Accessories (2 boxes) | |
| Orion mPulse 30 Upgraded ADL | Orion mPulse 30 joule pulse–arc welder with upgraded auto–darkening lens | |
| Orion mPulse 30 | Orion mPulse 30 joule pulse-arc welder with auto-darkening lens | |
| Orion Ear Ring Post Welder | | |

one

sun




- Orion EL 1.5 Tungsten Electrode Tips (15) 1.5mm.
- Orion EL 1.0 Tungsten Electrode Tips (15) 1.0mm.
- Orion EL 0.5 Tungsten Electrode Tips (15) 0.5mm.
- Orion EL 1.0/0.5 Tungsten Electrode Tips 1.0mm and 0.5mm (10 of each).
- Orion Collet 1.5mm 1.5mm Orion Collet
- Orion Collet 1.0mm 1.0mm Orion Collet
- Orion Collet 0.5 mm 0.5 mm Orion Collet





DESCRIPTION

PART NUMBER



| | sunstone | |
|--------------------------|--|-----------------|
| PART NUMBER | DESCRIPTION | PRODUCT PICTURE |
| Orion Gem Guard | SHG Gem Guard – 2 vial set | |
| Orion Weld Att. Pkg. | Orion Pulse Arc Weld Attachment Package. Includes: *Orion Pulse Arc Small Flat Peaked Pliers *Orion Tack Small Double Pole Tweezers *Orion Tack+ *Orion THP+ | |
| Orion Crosslock | Pulse Arc Cross Lock Tweezer | |
| Orion Brass Lined Pliers | Orion Brass Lined Pliers | |
| Orion Jump Ring Pliers | Jump Ring Pliers. | |
| Orion Double Pole | Orion Tack Small Double Pole Tweezers. | |



| Orion SPHP LP | Single Probe Hand Piece – Low Power. 1/4" dia brass shank accepts 1/16" (for Tungsten) or 2mm. | |
|---------------------------|--|--|
| Orion DPHP LP | Dual Probe Hand Piece – Low Power, 1/4" dia brass shank with10 AWG cabling, accepts 1/16" copper or 2mm tungsten electrodes (1 pair copper electrodes included). | |
| Orion THP+ | Orion Tweezer Hand Piece. 10 AWG Cabling (6 Feet) with Spade Connectors for use with Orion Welders. | |
| Orion Tack+ | Tack Welding Cables with + and – Alligator Clips. 10 AWG Cabling (6 Feet) with Spade Connectors for use with Orion Welders. | |
| Orion Tack Alligator Clip | Orion Tack Alligator Clip. 10 AWG cables (3 feet long), with spade terminals. For use with an Orion. | |

LASER WELDERS

PART NUMBER

LZR Combo 200 200J fiber laser welder with articulating arm

DESCRIPTION



LZR 60 60 Joule laser welder, with built in Camera.


LASER ENGRAVERS/CUTTERS

- LZR ENG 100 3D 100 Watt Laser Engraver for 3D parts.
- LZR ENG 50 3D 50 Watt Laser Engraver for 3D parts.
- LZR ENG 30 3D 30 Watt Laser Engraver for 3D parts
- LZR ENG 20 3D 20 Watt Laser Engraver for 3D parts









LZR ENG Vacuum Vacuum extractor for LZR Engraver

PULSE ARC COPPER WELDING SYSTEMS

DESCRIPTION

Orion 250i2 EV SystemOrion EV Welding System. Includes Orion 250i2 welder and WHEVPro 1 weld head, electrode starter kit, a Roll of SC500N10 Copper,
AGR-Inline, AGR2 & 1/4" argon tube splitter fitting.



Orion 250i2 EV Arm Pkg. Orion Swing Arm Microscope, Orion stylus & all standard Orion 250i2 accessories.


WHEV Jan 1

PART NUMBER

Includes all of the parts needed to complete the Orion 250i2EV system, that don't come included with a normal Orion 250i2. WHEV weld head, Steel collet nut, Brass nose cone with grounding cable, RJ11 connection cord, Base slide plate, Lower base and vertical upright that the WHEV head rides on, 2 black pressurized air hoses, 12v MAC valve, Argon splitter.







DC RESISTANCE WELDERS

Linear DC

PART NUMBER

Linear DC Welding power supply, with 12v MAC valve included, for ACS use. Intuitive touch screen, updateable, 10–2500amps, 0.01–500ms timing,



DUAL PULSE CD RESISTANCE WELDERS

DESCRIPTION

| CD1100DP | 1100ws Dual Pulse Industrial CD Spot Welder. |
|-------------|--|
| CD1100DP-RS | 1100 watt-second capacitive discharge spot welder with Roll Spot software. |



CD1000DP 1000ws Dual Pulse Industrial CD Spot Welder.

CD1000DP-RS 1000 watt-second capacitive discharge spot welder with Roll Spot software.





CD600DP600ws Dual Pulse Industrial CD Spot Welder.CD600DP-RS600 watt-second capacitive discharge spot welder with Roll Spot
software.CD400DP400ws Dual Pulse Industrial CD Spot Welder.CD400DP-RS400 watt-second capacitive discharge spot welder with Roll Spot
software.CD400DP-RS200 watt-second capacitive discharge spot welder with Roll Spot
software.CD200DP200ws Dual Pulse Industrial CD Spot Welder.CD200DP200ws Dual Pulse Industrial CD Spot Welder.CD200DP200ws Dual Pulse Industrial CD Spot Welder.CD200DP-RS200 watt-second capacitive discharge spot welder with Roll Spot
software.

SINGLE PULSE CD RESISTANCE WELDERS

DESCRIPTION

CD200SPM200ws Single Pulse Research and Light Production Resistance
Spot Welder.CD100SPM100ws Single Pulse Research and Light Production Resistance
Spot Welder.



AC RESISTANCE WELDERS

AC 15.0 kVA15kVA, 220–240v AC Welding Power Supply.AC 5.0 kVA5.0kVA, 220–240v AC Welding Power Supply.



AC 2.2 kVA

PART NUMBER

2.2kVA, 220–240v AC Welding Power Supply.





PART NUMBER DESCRIPTION

PRODUCT PICTURE

RESISTANCE WELDING WELD HEADS

WH1187A HF

WH1187 HF, High Force Opposed, MAC Valve Air-Actuated Weld Head with foot pedal, trigger cable, 1 AWG Welding Cables, 3/16" electrodes.

| WH1125A WH1125M | WH1125A Opposed, MAC Valve Air-Actuated Weld Head with foot pedal, trigger cable, 1 AWG Welding Cables, 1/8'' electrodes. WH1125M Opposed, Mechanical Weld Head with foot pedal, trigger cable, 1 AWG Welding Cables, 1/8'' electrodes. | |
|--------------------|---|--|
| WH1250 EL Upgrade | Opposed Weld Head 1/4" Electrode Holders and Electrodes. | |
| WH2125A WH2125M | WH2125A series/parallel, MAC Valve Air-Actuated Weld Head with foot pedal, trigger cable, 1 AWG Welding Cables, Glydcop electrodes (1 pair). Includes a base plate. WH2125M series/parallel, Manually-Actuated Weld Head with foot pedal, trigger cable, 1 AWG Welding Cables, Glydcop electrodes. | Notice of the second seco |
| WH2250 EL Upgrade | Parallel Weld Head 1/4" Electrode Holders and Electrodes. | |
| MWH3000 Opposed | Opposed Gap Micro Weld Head. Ranges between 350-3000gF. Manually Actuated. Includes Swing Arm & Microscope, 5x/10x Magnification with Light Source. | |
| MWH3000 Parallel | Parallel Gap Micro Weld Head. Ranges between 350–3000gF. | |

Parallel Gap Micro Weld Head. Ranges between 350–3000gF. Manually Actuated. Includes Swing Arm & Microscope, 5x/10x Magnification with Light Source.





PART NUMBER

DESCRIPTION

DECICTANCE WEI DINC HAND ATTACHMENTS

| RESISTANCE | VELDING HAND ATTACHWENTS |
|-------------------|--|
| PG1/2 | The PG1/2 is the smallest single side gun. It can be fitted with a straight or 90degree tip. Triggered with a foot pedal. Accepts threaded electrodes. |
| PG1 | The PG1 is the smallest single side gun. It can be fitted with a straight or 90 degree tip and has a built in switch. Accepts threaded electrodes. |
| PG2 | Pistol Grip Hand Piece with Button Trigger. Accepts threaded electrodes. |
| PG2W | The PG2W is a water cooled hand piece. Accepts threaded electrodes. Industrial uses. |
| PG3W | The PG3W is water cooled hand piece. Accepts compression electrodes. Heavy duty industrial uses. |
| PG4 | The PG4 gun is designed as a series welder. This gun will apply 2 spots simultaneously. Accepts compression electrodes. |
| PG5M | The PGSM miniature pliers, uses 1/8" electrodes. |
| EL PG Threaded | 3/8" Diameter, Tapered Copper Electrode (threaded) for PG2 and PG1. |
| EL PG Wheel | 2" Copper Wheel electrode, threaded fitting style. |
| EL PG Compression | 2" Copper Wheel electrode, compression fitting style. |



_

_

| PART NUMBER | DESCRIPTION | PRODUCT PICTURE |
|-------------------|--|-----------------|
| EL PG Adapter 125 | Threaded adapter for the Poke hand pieces, accepts a 1/8th inch electrode. | |
| EL PG Adapter 187 | Threaded adapter for the Poke hand pieces, accepts a 3/16th inch electrode. | |
| PASP2 | Pistol grip, pressure actuated single probe with adjustable pressure. | |
| PASP HP | Pressure–Actuated Single Probe Hand Piece Attachment with Large Alligator Clip for simple setup. | |
| PASP HP RS | Pressure-Actuated Single Probe Hand Piece Attachment (with Large Alligator Clip) for Roll Spot welding. Accepts 1/4'' dia electrodes, such as EL-Roll(included). | |
| EL-ROLL | Pressure-Actuated Single Probe Hand Piece Wheel | |
| SPHP | Single Probe Hand Piece | |
| SPHP LP | Single Probe Hand Piece – Low Power. 1/4'' dia brass shank accepts 1/16''(for Tungsten) or 2mm. | |
| SPHP MP | Single Probe Hand Piece – Medium Power, 5/8'' dia brass shank with 4 AWG cabling, accepts 1/8' electrodes. | |
| SPHP HP | Single Probe Hand Piece – High Power. 7/8'' dia brass shank accepts 3/16' electrodes. | |
| DPHP Micro | Micro Micro Welding Hand Piece for Use with DC Welders. Includes one thermal compression bonding hand piece with one MEL-TCB-FL electrode. *** For use with thermocompression electrodes. | |

×.



PART NUMBER

DESCRIPTION

as Argon.

| _ | | |
|---|--------------------|--|
| | DPHP | Dual Probe Hand Piece |
| | DPHP LP | Dual Probe Hand Piece – Low Power, 1/4" dia brass shank with 8 AWG cabling, accepts 1/16" copper or 2mm tungsten electrodes (1 pair copper electrodes included). |
| | DPHP MP | Dual Probe Hand Piece – Medium Power 5/8" dia brass shank with 4 AWG cabling, accepts 1/8" electrodes (1 pair copper electrodes included). |
| | DPHP HP | Dual Probe Hand Piece – High Power 7/8" dia brass shank with 1 AWG cabling, accepts 3/16" electrodes (1 pair copper electrodes included). |
| | Hand Piece Package | Hand Piece RWMA II Package includes Sunstone's DPHP, SPHP, & THP-A weld attachments. |
| | PTHP LP | Pressure-Actuated Tweezer Hand Piece: Low Power. 3/1''' diameter Electrodes. |
| | EL187RWMA-ANG | 3" Copper (Angled) Electrodes, 3/16" diameter (1 pair). |
| | EL187MOLY-ANG | 3" Molybdenum (Angled) Electrodes, 3/16" diameter (1 pair). |
| | PTHP MP | Pressure-Activated Tweezer Hand Piece: Moderate Power. 3/16" dia. Electrodes |
| | PTHP HP | Pressure-Activated Tweezer Hand Piece: High Power. 3/16" dia. Electrodes |
| | THP-P | Pneumatic Tweezer Hand Piece. |
| | ACS | Air Control System – Regulates Compressed Air Functionality for Pneumatic Weld Attachments, and Controls Shielding Gas such |



PART NUMBER

DESCRIPTION

| RESISTANCE | WELDING ELECTRODES | |
|---------------------|--|----|
| EL125BATT | 2.5" Battery Style Copper GlidCop Electrodes, 1/8" diameter (1 pair). | |
| EL250BATT | 2.5" Battery-Style Copper Glidcop Electrodes, 1/4" diameter (1 pair). | |
| EL062RWMA | 2" RWMA II Electrodes, 1/16" diameter (1 pair). | |
| EL125RWMA | 2" RWMA II Copper Electrodes, 1/8" diameter (1 pair). | |
| EL125RWMA3 | 3" RWMA III Electrodes, 1/8" diameter (1 pair). | |
| EL187RWMA | 2" Copper Electrodes, 3/16" diameter (1 pair). | |
| EL250RWMA | 2" Copper Electrodes, 1/4" diameter (1 pair). | |
| EL0625TUNG | 2" Pure Tungsten Electrodes, 1/16" diameter (1 pair). | 11 |
| EL125TUNG | 2" Pure Tungsten Electrodes, 1/8" diameter (1 pair). | |
| EL187TUNG | 2" Pure Tungsten Electrode, 3/16" diameter (1 Pair). | |
| EL125TUNG7 | 7" Pure Tungsten Electrodes, 1/8" diameter (1 pair). | // |
| EL187TUNG7 | 7" Pure Tungsten Electrodes, 3/16" diameter (1 Pair). | |
| EL125MOLY | 2" Molybdenum Electrodes, 1/8" diameter (1 pair). | // |
| EL187MOLY | 2" Molybdenum Electrodes, 3/16" diameter (1 pair). | |
| EL Honeycomb Flat | Honeycomb Tack Electrode Flat. | |
| EL Honeycomb Radius | Honeycomb Tack Electrode Radiused. | |
| MEL AG | Square, Adjustable Gap Glidcop Micro Electrodes for Micro Weld Head. 0.015'' x 0.025'' Face Tip (1 pair). Best for fine, Non coated, resistive wires. | |
| MEL AMO | Square, Adjustable Gap Molybdenum Micro Electrodes for Micro Weld Head. 0.015'' x 0.025'' Face Tip (1 pair) – Best for fine, Non coated, conductive wires. | |



| PART NUMBER | DESCRIPTION | PRODUCT PICTURE |
|----------------------------|---|-----------------|
| MEL BMO | Square, Fixed/Bonded 0.0015" Gap Molybdenum Micro Electrodes for Micro Weld Head. 0.010" x 0.010" Face Tip (1 pair). Best for very fine, Non coated, conductive wires. | |
| MEL TCB .25mm ² | Micro, thermocompression bonded electrode with a 0.25mm x 0.25mm flat face, 5 electrode pack. | |
| MEL TCB FL | 1/8" Tungsten Flat Thermal Compression Bonded Micro Electrodes (5 Pair). For use with fine magnet wires, using low voltages during welds. Medium range uses. | |
| MEL TCB SL | 1/8" Tungsten Slant Thermal Compression Bonded Micro Electrodes (S Pair). For use with fine magnet wires, using low voltages during welds. Designed to weld and 'cut' the wire simultaneously. | |
| MEL TCB SmFl | Micro, Thermocompression electrode with a small, flat face: 0.4mm x 0.5mm. Perfect for small magnet wires. (5 electrode pack). | |
| MEL TCB SY | 1/8" Tungsten Symmetrical Thermal Compression Bonded Micro Electrodes (5 Pair). For use with very fine magnet wires, using very low voltages during welds. Very precise. | |
| MEL TCB U | 1/8" Tungsten U-Shaped Thermal Compression Bonded Micro Electrodes (5 Pair). For use with larger magnet wires, using higher voltages during welds. | |

RESITANCE WELDING ACCESSORIES

ESHC

External Switch Hookup Cable.

Foot Switch – HDMI Foot Switch with HDMI connector for welders.

Foot Switch 3 Pin Foot Switch 3 Pin.

-



PART NUMBER

DESCRIPTION

BATTERY WELDING ACCESSORIES

| SNPSP | Nickel Precut Sample Pack. |
|-----------------|---|
| SN0625N34 0.08L | $0.0625^{\prime\prime}$ wide x $0.003^{\prime\prime}$ thick x $0.08^{\prime\prime}$ length pre-cut tabs . |
| SN125N34.8L | 0.125"w x 0.003"t x 0.80"L pre-cut nickel strip 250pc. |
| SN125N54.75L | 0.125"w x 0.005"t x 0.75"L pre-cut nickel strip 250pc. |
| SN250N54 1.125L | 0.25"w x 0.005"t x 1.125"L pre-cut nickel strip 250pc. |
| SN375N541.125L | 0.375"w x 0.005"t x 1.125"L pre-cut nickel strip 250pc. |



| SN Spooled Sample | Nickel Spool Sample Pack. |
|-------------------|--|
| SN0625N34 | 0.0625" x 0.003" Nickel Strip, 25 ft. spool. |
| SN125N34 | 0.125"w x 0.003"t x 25"L spooled nickel strip. |
| SN125N54 | 0.125"w x 0.005"t x 25"L spooled nickel strip. |
| SN250N54 | 0.250'w x 0.005"t x 25"L spooled nickel. |
| SN375N54 | 0.375" x 0.005" x 25"L spooled nickel strip. |



Spooled CopperCopper SpoolSC500N100.500"w x 0.010"t spooled copper strip.
25 ft. spool.

Fish Paper

8.75" x 11.75" Adhesive Fish Paper (10 sheets) 0.010 thick.



Shrink Wrap 100's of op Specificatio

100's of options available. Please inquire for prices. Specifications needed: diameter of tube, thickness of wall, color and length.



Mail:

Sunstone Welders 1693 American Way #5 Payson, UT 84651

Voice:

877-0786-WELD 877-786-9353 +1-801-658-0015

Fax:

866-701-1209

Email:

sales@sunstonewelders.com jason.davis@sunstonewelders.com